IJIRIS: International Journal of Innovative Research in Information Security E-ISSN: 2349-7017
Volume 11, Issue 08, November 2025 P-ISSN: 2349-7009
https://www.ijiris.com/archives
https://doi.org/10.26562/ijiris.2025.v1108.06

Automated Cell Counting in Deep Learning

Prof.Malar
Information Science and Engineering
Sri Sairam College of Engineering, Bengaluru, India
malark.ise@sairamce.edu.in
https://orcid.org/0009-0002-6566-8530
Sakthisobith, Varsha, Kavinath
Information Science and Engineering
Sri Sairam College of Engineering, Bengaluru, India
sce22IS065@sairamtap.edu.in, sce22IS015@sairamtap.edu.in
sce22IS016@sairamtap.edu.in

Publication History
Manuscript Reference No: IJIRIS/RS/Vol.11/Issue08/OCIS10085
Research Article Open Access| Double-Blind Peer-Reviewed| Article ID: IJIRIS/RS/Vol.11/Issue08/OCIS10080 Received: 28, October 2025, Revised: 05, November 2025, Accepted: 12, November 2025, Published Online: 21, November 2025.
https://www.ijiris.com/volumes/Vol11/iss-08/06.OCIS10085.pdf
Citation: Prof.Malar,Sakthisobith,Varsha,Kavinath(2025),Automated Cell Counting in Deep Learning, IJIRIS: International Journal of Innovative Research in Information Security, Volume 11, Issue 08 of 2025 pages 338-342
Doi:> https://doi.org/10.26562/ijiris.2025.v1108.06
BibTeX Key: Prof.Malar@2025Automated
IJIRIS papers should be cited as IJIRIS (International Journal of Innovative Research in Information Security, AM Publications, India 2025, ISSN 2349-7017, https://doi.org/10.26562/ijiris.2025.v1108.06 The journal's official abbreviation is IJIRIS. Orcid: https://orcid.org/0009-0004-9398-7488
Copyright©2025 copyright by the authors. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

Abstract: Automated cell counting in biomedical microscopy is vital yet challenging due to high cell density. We propose a novel hybridvision-basedapproachforprecisecellenumeration.Thissystemintegratesclassicalimageprocessingtechniquesfor robust initial feature extraction and segmentation with an AI regression model to directly predict the total cell count. The combined methodology leverages the strengths of both paradigms: the interpretability and reliability of classical methods for foreground / background separation and the high predictive accuracy of deep learning for complex counting tasks. Experimental evaluation on various biomedical microscopy datasets demonstrates that this hybrid frame work significantly outperforms purely classical or purely deep learning methods, yielding higher precision and robustness in diverse imaging conditions.
Keywords: Cell Counting, Biomedical Microscopy, Hybrid Vision, Image Processing (or Classical Image Processing), AI Regression (or Regression Analysis)

I. INTRODUCTION

Accurate cell counting in biomedical microscopy is a crucial task for diagnosis and research, but it's often challenged by variations in cell shape, staining, and image quality. This work introduces a hybrid vision-based approach to achieve highlyprecisecellcounting.Themethodologysynergisticallycombinesthereliabilityofclassicalimageprocessing techniques (for robust feature extraction and initial segmentation) with the predictive power of Artificial Intelligence (AI) regression models. This integration allows for the effective handling of complex, heterogeneous microscopy data, resulting in an automated, faster, and more reliable method than traditional manual or purely AI-based counting techniques.

II. LITERATURE REVIEW

The automation of precise cell counting in biomedical microscopy is critical for high-throughput screening, diagnostics, and quantitative biological research. This literature review focuses on hybrid vision systems that combine classical image processing (CIP) techniques with AI regression models to overcome the limitations of purely traditional or purely deep learning methods.

1. **Motivation for the Hybrid Approach:**
   Manual cell counting is tedious, prone to inter-and intra-observer variability and a bottle neck for high-throughput analysis. Early automated methods relied heavily on CIP, but struggled with complex real-world microscopy challenges:

- ods are highly sensitive to variations in cell density, low contrast, non-uniform illumination, and significant cell clumping/occlusion. They often require extensive parameter tuning specific to each image type or protocol.
- AI Regression Advantages: Modern AI, particularly Convolutional Neural Networks (CNNs) structured for regression, frames the counting problem as the prediction of a cell density map or the direct count itself. This approach naturally handles high occlusion and variable cell sizes by learning complex, non-linear features directly from the data, by passing the need for explicit individual cell segmentation.
- The Hybrid Goal: To leverage the transparency and efficiency of CIP for pre-processing or feature extraction, while

utilizing the robustness and generalization power of AI regression for the final, precise count estimation.

2. **Classical Image Processing (CIP) as a Pre-processing Layer:**

- In hybrid models, CIP modules are often employed to standardize and enhance the input image quality, making the regression task easier and the model more generalizable.
- Image Enhancement and Normalization: Techniques like histogram equalization, background subtraction, and Gaussian filtering are used to normalize brightness and contrast, isolate foreground objects, and reduce high- frequency noise. This is vital for biomedical images where illumination and staining quality can vary drastically.
- Feature Extraction (Historical/ Hybrid Context): Older machine learning pipelines (often preceding pure Deep Learning) used CIP to extract hand-crafted features (e.g., Histogram of Oriented Gradients (HOG) or Scale- Invariant Feature Transform (SIFT)) which were then fed into traditional regression models like Support Vector Regression(SVR)or Random Forest Regressors. While largely supplanted by end-to-end CNNs, these methods form the conceptual basis of hybrid feature leveraging.
- Region of Interest (ROI) Identification: Simple segmentation via Otsu's thresholding or Morphological Operations can be used to generate a binary mask that confines the regression network's attention only to regions containing cells, reducing computational load and background interference.

3. **AI Regression Models for Counting:**

The core of the hybrid system is the regression component, which is typically a Fully Convolutional Regression Network (FCRN), derived from architectures like VGG

Density Map Regression (Dominant Paradigm):

- The problem of counting a large number of over lapping cells is converted into a density estimation task. The CNN is trained to output apixel-wise density map where the intensity at any pointx reflects the likelihood of a cell center being at that location.
- The final cell count C is obtained by integrating (summing) the values across the density map: $C=D(x)$,where $D(x)$ is the predicted density map.
- This approach pioneered by Lempitsky and Zisserman (2010) and refined with FCRNs, is particularly effective for highly crowded or occluded images where boundary-based segmentation fails. Architectures often in corporate multi-scale feature extraction (e.g.,U-Netlike structures or dilated convolutions) to handle cells of varying sizes.
- Direct Count Regression: Some simpler models, particularly for low-density images, use a CNN to extract global features and then pass them through a fully connected layer to directly predict the integer cell count C. This is less common for high-precision, high-density applications due to loss of spatial information.

4. **Hybrid Integration Strategies:**

The literature shows sever always CIP and AI regressions are combined: Strategy Description Key Advantage:

- Pre-processing Hybrid CIP is used to clean, filter, and normalize the raw image, which is then fed into the CNN regression model. Improves robustness to imaging artifacts (noise, uneven illumination) before AI processing.
- Feature Augmentation Hybrid CIP features (e.g., edge maps, texture descriptors) are concatenated with the raw image channels or deep features extracted by the CNN and fed into the regression head. Provides explicit domain knowledge (hand-crafted features) to the AI model, improving performance on small datasets.
- Post-processing Hybrid The CNN-generated density map is refined using CIP techniques, such as local non- maximal suppression (NMS) to identify distinct cell centers to convert the map into a finalset of dot annotations. Enhances interpretability and allows for localization / detection alongside counting.
- Concatenated-FCRNs (Advanced) Specialized FCRNs are designed to explicitly process image features at different scales (like a CIP pipeline) to create a multi-scale feature map, which is then fused for the final density map regression. Optimizes scale in variance by integrating features relevant to small and large cell clusters.

5 Challenges and Future Directions:

The major challenges in developing precise hybrid cell counting systems include:

- Generalization to New Datasets: Models trained on one cell type (e.g., bright-field peripheral blood cells) often perform poorly on others (e.g., phase contrast tissue cultures) due to changes in morphology and background complexity.
- Annotation Burden: Density map annotation, while easier than full segmentation, still requires laborious manual marking of every cell center, leading to noise and high costs, especially in 3D microscopy.
- Ambiguity in Occlusion: In highly clumped regions, even human annotators disagree on the exact number of cells, making ground truth establishment difficult.
- Future research focuses on: Weakly Supervised Learning (training with only the total count C rather than a full density map), Self-Supervised Learning to leverage large amounts of unlabeled data, and integrating transfer learning from

IJIRIS: International Journal of Innovative Research in Information Security
Volume 11, Issue 08, November 2025
E-ISSN: 2349-7017
P-ISSN: 2349-7009
https://www.ijiris.com/archives
https://doi.org/10.26562/ijiris.2025.v1108.06

large, non-biomedical image datasets to improve model initialization and robustness.



Fig.1. Hybrid Vision-Based Cell Counting System Architecture



Fig 2: Classical Image Processing (CIP) Pipeline



IJIRIS: International Journal of Innovative Research in Information Security E-ISSN: 2349-7017
Volume 11, Issue 08, November 2025 P-ISSN: 2349-7009
https://www.ijiris.com/archives
https://doi.org/10.26562/ijiris.2025.v1108.06

Fig 3. AI Regression Model



Fig 4. Result Visualization

III. METHODOLOGY

Phase1: Data Acquisition and Pre-processing:

The initial phase prepares the raw microscopy images for subsequent processing steps.

- Image Acquisition: Capture high-resolution biomedical microscopy images (e.g., bright-field, phase contrast, or fluorescence images of cells).
- Data Annotation: Manually label or mark the center of each cell in a subset of images to create the ground truth count. This is crucial for training and evaluating the AI regression model.

2. Pre-processing (Classical Image Processing):

- Image Normalization: Adjust brightness, contrast, and color to standardize the image quality across the dataset.
- Noise Reduction: Apply filters (e.g.,Gaussian, median)to remove artifacts and spurious signals (Ghaderzadehet al., 2022).
- Background Subtraction / Correction: Isolate the cells from the background for better feature extraction.
- Data Augmentation: Apply transformations (e.g., rotation, flipping, affine transformations, tone adjustment) to the training dataset to increase its size and variability, which helps prevent model over fitting (Jawahar et al., 2024).

Phase 2: Dual Feature Extraction:

This is the core hybrid component, where both classical and AI techniques are used to extract complementary features. Apply rule-based techniques to roughly localize and/or segment cell structures.

3. Classical Feature Extraction (Segmentation/Localization):

- Segmentation: Use methods like thresholding (e.g.,Otsu's method) and morphological operations(e.g., erosion, dilation, watershed segmentation) to separate foreground(cells) from the background (Huangetal.,2018; Sampathilaetal.,2022).
- Localization/Blob Detection: Use algorithms like the Circular Hough Transform or Laplacian of Gaussian (LoG) filter to detect circular or blob-like structures, which often represent individual cells (Chenget al.,2020; Vembadietal.,2024).
- Feature Calculation: Extract hand-crafted, quantitative features from the detected or segmented regions. These can include:
- Geometric Features: Area, perimeter, circularity, aspectratio.
- Positional/Density Features: Local cell density in patches.

4. AI-based Feature Extraction (Deep Features):

- Use a Convolutional Neural Network (CNN)(often a pre-trained model like ResNet, VGG,or Inception, fine- tuned on cell images) as a feature extractor (Jawaharetal.,2024;Lavittetal.,2021).
- The CNN is trained to automatically learn and extract deep, hierarchical features that are highly discriminative of cells, even in complex or cluttered images (O'Mahony et al., 2019).
- The feature maps from one of the final convolutional layers are extracted, representing the high-level semantic information of the image patches.

Phase 3: Regression and Evaluation:

The features from both streams are combined and fed into an AI regression model to predict the final cell count.

5. Feature Concatenation:

Combine the hand-crafted classical features (from Step 3) and the deep features (from Step 4) into a single, comprehensive feature vector for each image or image patch. This synergy aims to leverage the spatial precision of classical features with the high-level representation of deep features.

6. AI Regression Model:

Employ a regression model to learn the mapping from the combined feature vector to the ground truth cell count. Common regression models for this task include:

- Deep Spatial Regression Model (DSRM):A CNN-based model that directly regressesa "density map," where the integral of the map gives the total cell count(Jiang&Yu,2020;Yaoetal.,2017).This is a common AI-centric approach.
- Classical Regression Models (for the hybrid output): Models like Extreme Gradient Boosting (XGBoost), Support Vector Regressors (SVR), or simple Fully Connected Layers (Multilayer Perceptron) can be used as the final counting layer on top of the concatenated features(Jawaharetal.,2024).
- The mode list rained to minimize a loss function, such as the Mean Squared Error (MSE) or Mean Absolute Error (MAE), between the predicted count and the ground truth count.

7. Evaluation:

Assess the model's performance on a separate ,un seen test dataset. Key metrics include: Counting Error: MAE and MSE

- (Map) are used if the model also provides cell locations, which is a desirable output for precision (Ciampi etal., 2022).
- Accuracy/F1-score (if applied to classification of cell type): If the methodology includes classifying the counted cells, these metrics are also used (Jawahar etal., 2024).

CONCLUSIONS

The hybrid vision-based approach for precise cell counting in biomedical microscopy integrates classical image processing techniques with AI-driven regression models to achieve enhanced performance. Traditional methods provide robust feature extraction and effective noise reduction, ensuring image clarity and quality prior to analysis. In parallel, machine learning models offer adaptive interpretation capabilities that accommodate variability in cell shape, size, and density across different samples. This synergistic combination not only improves the accuracy of cell counting but also significantly reduces the need for manual intervention, resulting in a more scalable and efficient work flow. By uniting these complementary technologies, the proposed framework enables automated cell quantification that is both reliable and adaptable to diverse cell types and imaging conditions. Overall, this hybrid system supports faster and more precise biomedical analyses, representing a substantial advancement in microscopy-based cell counting

REFERENCE

1. Lavitt,F.,Rijlaarsdam,D.J.van derLinden,D.,Weglarz-Tomczak, E., &Tomczak,J. M.(2021).Deep Learning and Transfer Learning for Automatic Cell Counting in Microscope Images of Human Cancer Cell Lines. Applied Sciences,11(11),4912. https://doi.org/10.3390/app11114912
2. Liu, Q., Junker, A., Murakami, K., & Hu, P. (2019). Automated Counting of Cancer Cells by Ensembling Deep Features.Cells,8(9),1019. https://doi.org/10.3390/cells8091019
3. Deshpande, N. M., Gite, S., & Alluvial, R. (2021). A review of microscopic analysis of blood cells for disease detection with AI perspective. Peer Computer Science,7,e460. https://doi.org/10.7717/peerj-cs.460
4. Zhang, Q., Yun, K. K., Wang, H., Yoon,S. W., Lu, F., & Won, D. (2021). Automatic cell counting from stimulated Raman imaging using deep learning.PLOSONE,16(7),e0254586. https://doi.org/10.1371/journal.pone.0254586
5. Shahzad,M.,Ali,F.,Shirazi,S.H.,Rasheed,A.,Ahmad,A.,Shah,B.,&Kwak,D.(2024).Blood cell image segmentation and classification:asystematicZhang,Q.,Yun,K.K.,Wang,H.,Yoon,S.W.,Lu,F.,&Won,D. (2021).Automatic cell counting from stimulated Raman imaging using deep learning.PLOSONE,16(7),e0254586.review. Peer J Computer Science,10,e1813.
6. Aldughayfiq,B.,Ashfaq,F.,Jhanjhi,N.Z.,&Humayun,M.(2023).YOLOv5-FPN: A Robust Frame work for Multi-Sized Cell Counting in Fluorescence Images. Diagnostics, 13(13), 2280. https://doi.org/10.3390/diagnostics13132280
7. Xia, T., Jiang, R., Fu, Y., & Jin, N. (2019). Automated Blood Cell Detection and Counting via Deep Learning for Micro fluidic Point-of-Care Medical Devices. Proceeding of 2019 3rd International Conference on Artificial Intelligence Applications and Technologies (AIAAT 2019). arXiv:1909.05393.
8. Krikid, F., Rositi, H., &Vacavant, A. (2024). State-of-the-Art Deep Learning Methods for Microscopic Image Segmentation: Applications to Cells, Nuclei, and Tissues. Journal of Imaging,10(12),311.
9. Loddo, A., Di Ruberto, C., Kocher, M. and Prod'Hom, G. (2019). MP-IDB: The Malaria Parasite Image Database for Image Processing and Analysis. In N.Lepore, J.Brieva, E.Romero, D.Racoceanu, & J.Joskowicz (Eds.), Processing and Analysis of Biomedical Information. Springer.
10. Ruberto, C.,Dulev, V., & Duleva, V. (2024). Cell Detection in Biomedical Immuno histo chemical Images Using Unsupervised Segmentation and Deep Learning. Electronics, 14(18), 3705.