IJIRIS: International Journal of Innovative Research in Information Security E-ISSN: 2349-7017
Volume 12, Issue 03, March 2026 P-ISSN: 2349-7009
https://www.ijiris.com/archives
https://doi.org/10.26562/ijiris.2025.v1203.02

Accident Detection and Alert System

V.MahaLakshmi
Assistant Professor, Department of Information Technology
Sengunthar Engineering College,Tiruchencode,India
vmahalakshmi.it@scteng.co.in
https://orcid.org/0009-0005-4313-0520
Madhan D,Prasanna P,Sivanesh S,Sugilarasu T
Department of Information Technology
Sengunthar Engineering College,Tiruchencode, India

Publication History
Manuscript Reference No: IJIRIS/RS/Vol.12/Issue03/ISMR26.MRIS10081
Research Article Open Access| Double-Blind Peer-Reviewed| Article ID: IJIRIS/RS/Vol.12/Issue03/ISMR26.MRIS10081
Received: 31, January 2026, Revised: 14, February 2026, Accepted: 17, March 2026, Published Online: 25,March 2026.
https://www.ijiris.com/volumes/Vol12/iss-03/02.ISMR26.MRIS10081.pdf
Article Citation: MahaLakshmi,Madhan,Prasanna,Sivanesh,Sugilarasu(2026),Accident Detection and Alert System,IJIRIS: International Journal of Innovative Research in Information Security,Volume 12, Issue 03 of 2026 pages 88-91
Doi:> https://doi.org/10.26562/ijiris.2026.v1203.02
BibTeX Key: MahaLakshmi@2026Accident
IJIRIS papers should be cited as IJIRIS (International Journal of Innovative Research in Information Security,AM Publications, India 2026, ISSN 2349-7017, https://doi.org/10.26562/ijiris.2026.v1203.02 The journal's official abbreviation is IJIRIS. Orcid: https://orcid.org/0009-0004-9398-7488
Copyright©2026 copyright by the authors.This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

Abstract: Road accidents are among the leading causes of death and serious injury worldwide, representing a critical public safety challenge that continues to escalate with increasing urbanization and vehicle density. Every year, millions of people lose their lives or suffer life-threatening injuries due to delayed medical attention following road accidents. In most cases, the time gap between the occurrence of an accident and the arrival of medical help plays a decisive role in determining the survival and recovery of victims. Unfortunately, in many road accident scenarios, immediate reporting does not occur, especially when the victim is unconscious or when the accident happens in remote areas. Hence, there is an urgent need for an intelligent system that can automatically detect accidents and send alerts in real time without human intervention. This necessity forms the foundation of the Accident Detection and Alert System, which aims to leverage modern sensor technologies, Global Positioning System (GPS), and Global System for Mobile Communication (GSM) modules to enhance road safety and minimize casualties caused by delayed emergency response. The Accident Detection and Alert System is an innovative embedded system designed to automatically detect road accidents, identify their location, and instantly notify emergency services or predefined contacts. The system primarily relies on sensors such as an accelerometer and vibration sensor to monitor vehicle motion and detect abnormal impacts. The accelerometer continuously records acceleration in multiple axes, and any sudden deviation from normal thresholds indicating a collision or rollover is treated as a potential accident. In parallel, the vibration sensor provides an additional confirmation by detecting the magnitude of vibration or shock. Once an accident is detected, the microcontroller processes the data and retrieves the exact geographical coordinates from the GPS module. These coordinates, along with predefined alert message, are then transmitted via the GSM module to emergency contacts or rescue teams.

1. INTRODUCTION

Nowadays, the rate of accidents has increased rapidly. Due to employment, the usage of vehicles like cars, bikes have increased, because of this reason the accidents can happen due to over speed. People are going under risk because of their over speed, due to unavailability of advanced techniques, the rate of accidents can't be decreased. To reduce the accident rate in the country this paper introduces a solution. Automatic accident detection and alert systems are introduced. The main objective is to control the accidents by sending a message to the registered mobile, hospital and police station using wireless communications techniques. When an accident occurs in a city or any place, the message is sent to the registered mobile through GSM module in less time. Arduino is the heart of the system which helps in transferring the message to different devices in the system. Vibration sensor will be activated when the accident occurs and the information is transferred to the registered number through the GSM module. The GPS system will help in finding the location of the accident spot. The proposed system will check whether an accident has occurred and notify nearest medical centers and registered mobile numbers about the place of accident using GSM and GPS modules. The location can be sent through a tracking system to cover the geographical coordinates over the area. The accident can be detected by a vibration sensor which is used as a major module in the system. Road accidents are one of the leading causes of death and serious injuries worldwide. The growing number of vehicles and the rise in reckless driving, poor road conditions, and lack of immediate emergency response have made road safety a major concern. In many accident cases, the delay in providing medical assistance due to late reporting is the primary reason for the loss of lives.

IJIRIS: International Journal of Innovative Research in Information Security E-ISSN: 2349-7017
Volume 12, Issue 03, March 2026 P-ISSN: 2349-7009
https://www.ijiris.com/archives
https://doi.org/10.26562/ijiris.2025.v1203.02

1.1 OBJECTIVE

The primary objective of the Accident Detection and Alert System is to design and develop an intelligent, efficient, and reliable system that can automatically detect road accidents and immediately send alerts to emergency services and nearby contacts, thereby minimizing response time and potentially saving lives. The system aims to bridge the gap between the occurrence of an accident and the arrival of emergency assistance by using modern technologies such as sensors, GPS, GSM, and microcontrollers.

1.2 PROBLEM IDENTIFICATION

Road accidents have become one of the most serious issues worldwide, causing significant loss of life, property damage, and emotional distress. Every year, thousands of people die in traffic accidents, and many more suffer permanent injuries. One of the major reasons for these fatalities is the delay in providing medical assistance after an accident occurs. In most cases, when an accident happens in an isolated area or during late hours, there are no bystanders available to report the incident immediately. As a result, emergency services are informed too late, reducing the chances of survival for the victims. Traditional accident reporting systems depend heavily on human intervention, where someone must witness the accident and contact emergency services manually

1.3 SCOPE / OUTCOM

The Accident Detection and Alert System has a wide scope in the field of intelligent transportation and road safety. With the rapid increase in the number of vehicles and road accidents, there is an urgent need for an automated, reliable, and efficient system that can detect accidents instantly and notify emergency services without any human involvement. This project aims to design a system capable of detecting accidents accurately using sensors, processing the data through a microcontroller, and sending the accident location and alert message to concerned authorities or family members through GSM and GPS technologies. The scope of this system extends across personal, commercial, and public transportation sectors. It can be implemented in all types of vehicles such as cars, trucks, buses, and motorcycles. The system is not limited to detecting major collisions but can also be calibrated to recognize different levels of impact severity. In the event of an accident, the system automatically collects real-time data, determines the vehicle's exact GPS location, and transmits this information to pre-defined emergency contacts, hospitals, or traffic control centers. This ensures that help reaches the victim as quickly as possible, thereby reducing the fatality rate and minimizing injury severity.

2. MODULES

The Accident Detection and Alert System is composed of several integrated modules that work together to detect accidents, determine location, and send alerts to emergency contacts. Each module performs a specific function, and the proper coordination among them ensures the system's reliability and efficiency. The major modules of this project include:
models are then trained using large datasets containing text, images, and scientific data. After training, the models undergo testing and evaluation to ensure accuracy and reliability. Fine-tuning techniques are applied to improve performance before the models are deployed into the system. Continuous monitoring is performed to maintain system performance and detect potential errors or biases.

1. Sensor Module

The Sensor Module is the core component responsible for detecting accidents. It typically uses an accelerometer and vibration sensor to monitor the vehicle's motion and detect sudden changes in acceleration or impact force. When the vehicle experiences an unusual jerk, high impact, or rapid deceleration, the sensor recognizes this as a potential collision. The sensor readings are continuously sent to the microcontroller for further analysis. In more advanced systems, a gyroscope may also be added to detect angular tilt, which helps identify rollover accidents. This module ensures accurate and instant accident detection.

2. Microcontroller Module

The Microcontroller Module acts as the brain of the entire system. It processes the data received from the sensors and decides whether an accident has occurred. If an abnormal condition is detected, it activates the alert mechanism. Popular microcontrollers such as Arduino Uno, ESP32, or Raspberry Pi can be used for this purpose. The microcontroller also coordinates with other modules like the GPS and GSM modules to collect and transmit the required information. It ensures logical decision-making and smooth operation of the system.

3. GPS Module

The Global Positioning System (GPS) Module is responsible for determining the exact geographical coordinates (latitude and longitude) of the vehicle at the time of the accident. Once the microcontroller identifies a collision, the GPS module is triggered to capture the vehicle's real-time location. This information is crucial for emergency services to locate the accident site quickly and accurately. Modern GPS modules offer high precision and can operate even in remote areas with limited connectivity.

4. GSM Module

The Global System for Mobile Communication (GSM) Module handles the communication aspect of the system. Once an accident is confirmed, this module automatically sends an alert message containing the vehicle's GPS location, accident time, and possibly the vehicle ID to pre-defined emergency contacts such as family members, hospitals, or police stations. The message can be sent as an SMS or via network data depending on the system configuration. This module ensures that the alert reaches the concerned authorities without any manual intervention.

IJIRIS© 2014-26, AM Publications - All Rights Reserved

IJIRIS: International Journal of Innovative Research in Information Security E-ISSN: 2349-7017
Volume 12, Issue 03, March 2026 P-ISSN: 2349-7009
https://www.ijiris.com/archives
https://doi.org/10.26562/ijiris.2025.v1203.02

3. SYSTEM ANALYSIS

3.1. Existing System Analysis

In the traditional scenario, accident reporting heavily depends on human participation. When an accident occurs, it is usually reported by bystanders or other road users who witness the event. This manual process is slow and unreliable, especially when accidents happen in remote areas or at night where there are no witnesses. In some cases, the victims may be unconscious or unable to call for help, leading to critical delays in receiving medical attention. Moreover, the lack of precise location information further complicates rescue operations, making it difficult for emergency teams to reach the accident site quickly. These limitations highlight the inefficiency of the existing manual system and the need for an automated accident detection and alert mechanismmultiple scientific domains or running complex simulations.

3.2. Proposed System Analysis

The proposed Accident Detection and Alert System aims to overcome these challenges by integrating sensors, GPS, GSM, and a microcontroller into a single intelligent unit. The system continuously monitors vehicle movements through accelerometer and vibration sensors. When a sudden impact or deviation from normal motion is detected, it is interpreted as an accident. The microcontroller processes this data and immediately triggers the alert process. The GPS module determines the exact geographical location of the vehicle, while the GSM module transmits this information to predefined contacts such as emergency services, family members, or hospitals through SMS or network communication.

3.3. System Requirements Analysis

The system requires both hardware and software components to function effectively. The hardware components include a microcontroller (e.g., Arduino Uno or ESP32), accelerometer sensor, GPS module, GSM module, power supply, and an optional display or buzzer. On the software side, the system uses embedded C or Python programming for sensor integration, data processing, and communication control. The requirements are chosen to ensure accuracy, speed, and cost efficiency.

3.4 Functional Analysis

The system performs several key functions: Accident Detection: Continuous monitoring of vehicle acceleration and orientation using sensors. Location Tracking: Real-time determination of the accident location using GPS coordinates. Alert Transmission: Automatic sending of alert messages to emergency contacts through the GSM module. User Notification: Optional display or buzzer alert to indicate successful message transmission. Each function is designed to operate in real-time, ensuring reliability and minimal delay during emergencies

3.5. System Requirements

The Accident Detection and Alert System requires both hardware and software components to operate efficiently and reliably. Each requirement is carefully chosen to ensure the system's accuracy, speed, low power consumption, and cost-effectiveness. This section outlines the hardware and software requirements, along with their respective functions in the overall system design.

4. SYSTEM IMPLEMENTATION

The System Design and Implementation of the Accident Detection and Alert System focuses on creating a reliable and efficient structure that integrates various hardware and software components to detect accidents and send alerts automatically. The system is designed to be cost-effective, modular, and capable of operating in real-time to ensure timely communication with emergency responders. processing, computer vision, data analytics, and intelligent simulations into one unified framework. The system acts as a centralized digital intelligence capable of processing information, learning from various data sources, and assisting users across multiple domains.

4.2. System Design Overview

The system design includes two main aspects: hardware design and software design.

- Hardware Design deals with selecting and interfacing different components such as sensors, microcontroller, GPS, GSM modules, and the power supply.
- Software Design involves developing embedded programs to control the hardware modules, process sensor data, and automate alert communication.

4.3. Hardware Design

The hardware design is the backbone of the system. It consists of the following key modules:

Microcontroller Unit:

The microcontroller (e.g., Arduino Uno, PIC, or ATmega328P) acts as the central processing unit. It collects sensor data, processes it, determines whether an accident has occurred, and controls the communication modules.

Accelerometer and Vibration Sensors:

These sensors continuously monitor the vehicle's movement and vibration levels. The accelerometer detects sudden changes in speed and direction, while the vibration sensor identifies impact force

5. WORKING PRINCIPLE

The Accident Detection and Alert System is designed to automatically detect vehicular accidents in real time and immediately send alerts to emergency services and predefined contacts. The system operates on the integration of sensors, microcontrollers, communication modules, and GPS technology to provide a reliable and quick response during road accidents. The working of this system can be divided into five main stages: Sensing, Processing, Detection, Communication, and Alert Generation.

1. Sensing Stage

In the initial stage, the system continuously monitors the vehicle's condition and movement using various sensors such as an accelerometer, gyroscope, and GPS module. The accelerometer measures the change in acceleration of the vehicle. The gyroscope detects angular rotation or sudden changes in orientation. The GPS module tracks the exact geographical coordinates and speed of the vehicle. Under normal driving conditions, these sensors produce data that remain within safe thresholds. When an accident occurs, such as a sudden collision, rollover, or abrupt deceleration, the sensor readings spike beyond predefined limits.

2.Processing Stage

The sensor data is sent to the microcontroller unit (MCU) for processing. The microcontroller acts as the brain of the system. It continuously analyzes sensor input and compares the data against accident threshold values. If the measured acceleration or angular change exceeds a critical level, the microcontroller interprets it as a possible collision event. To ensure accuracy and reduce false positives (like hitting a speed breaker or pothole), the system performs multiple checks using data filtering algorithms and cross-verifies the GPS speed data. Once the microcontroller confirms an accident has occurred, it activates the accident detection routine. The system can also include a manual confirmation mechanism such as a button or timer delay (for example, 10 seconds) to cancel false triggers if the driver is safe. If no manual response is received within the set time, the system assumes a real accident situation.

6. CONCLUSION

The Accident Detection and Alert System developed in this project successfully fulfills its primary objective of detecting vehicle accidents and sending alert messages containing the precise location to predefined contacts. The integration of sensors such as the accelerometer and vibration sensor ensures accurate detection of sudden impacts, while the GPS and GSM modules enable reliable transmission of real-time location data. The system demonstrated high accuracy, quick response, and consistent reliability during testing, with minimal false alarms. By automating accident detection and emergency alerting, the system provides a faster means of notifying rescue authorities or family members, potentially reducing response time and saving lives. The modular design and microcontroller-based approach make it cost-effective, portable, and adaptable for various vehicle types. Overall, the developed system proves to be an efficient and dependable solution for enhancing road safety and improving post-accident response.